LD-18 WATER LEAK DETECTOR



FEATURES

- All-digital amplifier, with automatic noise reduction of intermittent sounds, high and low filters, storage and graphing of sound levels at different locations on the pipe, bar graph and numeric display of sound loudness, USB connection, and back light.
- Automatic noise reduction capability for intermittent noises such as pedestrian footsteps, people talking, and passing vehicles.
- Storage and graphical display of the leak's loudness at multiple locations along the pipe.
- Large LCD Display, provides superior visibility in both direct sunlight and dark environments.
- 5 High Frequency filters, 3 Low Frequency filters (plus Low filter OFF), and 2 Notch filters (plus Notch filter OFF) to remove continuous interfering noises from A/C hum, motors, wind, etc.
- ▶ Hard ABS plastic carrying case included.
- > Soft padded case and waist strap for the transmitter.



Includes:

- → ABS custom case
- ⊳ Screw driver
- ⊳ Waist strap
- Instruction manual

SPECIFICATIONS

AMPLIFIER

Combined Sensitivity:

▶ Low Filters:

▶ High Filters:

▶ Notch Filters:

▶ Maximum No. of Sound:

▶ Power:

▶ Battery Life:

▶ Frequency Range:

▶ Weight:

Size:

▶ Weather Resistance:

▶ Temperature Range:

SENSOR

➤ Type:

▶ Weather Resistance:

Standard Base:

900 V/G or higher (at 400 Hz)

and Amplification

Off, 100 Hz, 200 Hz, 400 Hz

400 Hz, 600 Hz, 800 Hz,

1200 Hz, 2200 Hz

Off, 50 Hz, 60 Hz

250 (by date and time)

Levels Saved in File

4 C dry cell batteries

24 hours minimum

(continuous use)

50 Hz to 2200 Hz

35 ounces (including 4 C batteries)

6.4"w x 3.0"h x 5.7"d

(163mm x 76mm x 145mm)

IP52 equivalent

Minus 4 F to Positive 130 F

(Working)

Piezo electric ceramic

IP67 equivalent

(3 ft water depth for 30 minutes)

3 - Pronged Plate

(removable with nutdriver)



