

40mm Pipe Inspection Camera System

**SUBSURFACE
INSTRUMENTS, INC**

Premier developer, manufacturer and distributor of high frequency and magnetic locators, PVC pipe detectors, PE Pipe, metallic pipe, cable and custom specialty locators.



Camera Head	
Camera Size:	ø40mmX86mm
Spring length:	ø22.3mmX160mm
Self-leveling Function	
Sensor size:	1/4 inch
View angle:	105°
Work current/supply:	DC12V
Camera light:	42PCS white LEDs
Resolution:	PAL: 720X576 NTSC: 720X480
Glass material:	Sapphire glass
Shell material:	Aluminum Alloy
Cable Wheel	
Cable size:	520(L)X320(W)X710(H)
Wire material:	Fiberglass rod
Wire length:	60m
Wire diameter:	ø9.0mm
Wheel material:	Stainless steel
Meter counter & handle-brake	
Fiberglass color:	Yellow

Monitor	
Size:	9inch digital color
Total Pixels:	1440X234
Work current/supply:	250MA / DC12V
OSD language:	English
Image reversible	
Model:	16:9&4:3
Sunshade	
Li-ion Battery	
Total Power:	14W
Charge time:	5hours
Protective voltage:	8.1V
Work time:	≥260minutes
Suitcase	
size:	L460XW370XH180mm
Material:	Engineering plastics
Charger	
Input:	AC100-240V~50/60Hz
Output:	DC 12V/1000MA
DC plug diameter:	2.1mm

Control Box	
Power supply:	12V
Work current:	200MA
Storage medium:	8G SD card(max 32G) SD card reader
Battery level display	
Picture snap & movie record	
DVR Total Pixels:	720X576 (D1)
Movie format:	AVI
Microphone Audio record	
Stereo earphone output	
Keyboard	
Size:	220X118X18mm
Language:	English
Interface:	USB
Text Edit Line:	PAL 27 letter 14 line NTSC 27 letter 12 line
Max Edit Page:	4 pages
Skids	
Skid	ø110 mm / ø150 mm / ø220 mm



SubSurface Instruments, Inc. | 1230 Flightway Drive, De Pere, WI. 54115
toll free: 855.422.6346 | Website: www.ssilocators.com | email: info@ssilocators.com

Updated 02/05/2019

